



2TB-GSP

BSPT MALE / BSP FEMALE PRESSURE GAUGE CONNECTORS

PART NO.	THREAD		COPPER WASHER	DIMENSIONS				
	E	F		A	B	L	S1	S2
2TB-02-04GSPZ	R1/8"X28	G1/4"X19	DP-B04G	10	14.5	24.5	12	19
2TB-04GSPZ	R1/4"X19	G1/4"X19	DP-B04G	14.5	12	29	17	19
2TB-04-08GSPZ	R1/4"X19	G1/2"X14	DP-B08G	14.5	16	31.5	19	27
2TB-06-04GSPZ	R3/8"X19	G1/4"X19	DP-B04G	15	12	29.5	19	19
2TB-08-04GSPZ	R1/2"X14	G1/4"X19	DP-B04G	20	12	36.5	22	19
2TB-08GSPZ	R1/2"X14	G1/2"X14	DP-B08G	20	16	39	22	27

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2TB-08GSPZ
304 stainless steel	SR	2TB-08GSPSR
316L stainless steel	SV	2TB-08GSPSV
316Ti stainless steel	SY	2TB-08GSPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2TB-08GSPZ	96	360
Durakote plating	ZD	2TB-08GSPZD	360	720
Zinc-nickel plating	ZN	2TB-08GSPZN	1000	-