



9B

BSP FEMALE 60° CONE PLUG

PART NO.	THREAD			DIMENSIONS				
	E			A	L	S2		
9B-02Z	G1/8"X28			5.5	11.5	14		
9B-04Z	G1/4"X19			5.5	13.5	19		
9B-06Z	G3/8"X19			6.3	14.5	22		
9B-08Z	G1/2"X14			7.5	16	27		
9B-10Z	G5/8"X14			9.5	16.5	30		
9B-12Z	G3/4"X14			10.9	17.5	32		
9B-16Z	G1"X11			11.7	19	41		
9B-20Z	G1.1/4"X11			10.1	21.5	50		
9B-24Z	G1.1/2"X11			12.5	22	55		
9B-32Z	G2"X11			16.1	26.5	70		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	9B-08Z
304 stainless steel	SR	9B-08SR
316L stainless steel	SV	9B-08SV
316Ti stainless steel	SY	9B-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	9B-08Z	96	360
Durakote plating	ZD	9B-08ZD	360	720
Zinc-nickel plating	ZN	9B-08ZN	1000	-