


6F



6F-LN

ORFS MALE O-RING BULKHEAD

REF. ISO 8434-3

PART NO.		THREAD		O-RING		DIMENSIONS				
BODY	ASSEMBLY	E	F	LEFT	RIGHT	A	B	L	S1	S2
6F-04Z	6F-04LNZ	9/16"X18	9/16"X18	O011	O011	10	31.5	48.2	22	22
6F-06Z	6F-06LNZ	11/16"X16	11/16"X16	O012	O012	11.2	34	53.2	27	27
6F-08Z	6F-08LNZ	13/16"X16	13/16"X16	O014	O014	13	36.5	58.3	30	30
6F-10Z	6F-10LNZ	1"X14	1"X14	O016	O016	15.5	40.6	66.6	36	36
6F-12Z	6F-12LNZ	1.3/16"X12	1.3/16"X12	O018	O018	17	41.7	69.2	38	38
6F-16Z	6F-16LNZ	1.7/16"X12	1.7/16"X12	O021	O021	17.5	42.2	70.2	46	46
6F-20Z	6F-20LNZ	1.11/16"X12	1.11/16"X12	O025	O025	17.5	42.2	70.2	50	50
6F-24Z	6F-24LNZ	2"X12	2"X12	O029	O029	17.5	42.2	70.2	60	60

1. Material options for connector body and nut, O-ring.

Connector body and nut material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	6F-10Z
304 stainless steel	Viton	SR	6F-10SR
316L stainless steel	Viton	SV	6F-10SV
316Ti stainless steel	Viton	SY	6F-10SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	6F-10Z	96	360
Durakote plating	ZD	6F-10ZD	360	720
Zinc-nickel plating	ZN	6F-10ZN	1000	-