



5JB-G

JIC MALE 74° CONE/BSP PRESSURE GAUGE CONNECTOR

PART NO.	THREAD		COPPER WASHER		DIMENSIONS					
	E	F		F	A	L	S1			
5JB-04-08GZ	7/16"X20	G1/2"X14		DP-B08G	14	41	27			
5JB-04GZ	7/16"X20	G1/4"X19		DP-B04G	14	32	19			
5JB-05-04GZ	1/2"X20	G1/4"X19		DP-B04G	14	28	19			
5JB-05-08GZ	1/2"X20	G1/2"X14		DP-B08G	14	41	27			
5JB-06-04GZ	9/16"X18	G1/4"X19		DP-B04G	14.1	28.1	19			
5JB-06-08GZ	9/16"X18	G1/2"X14		DP-B08G	14.1	35.5	27			
5JB-08-04GZ	3/4"X16	G1/4"X19		DP-B04G	16.7	31	22			
5JB-08GZ	3/4"X16	G1/2"X14		DP-B08G	16.7	38	27			
5JB-10-08GZ	7/8"X14	G1/2"X14		DP-B08G	19.3	40.5	27			
5JB-12-08GZ	1.1/16"X12	G1/2"X14		DP-B08G	21.9	43	30			

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5JB-08GZ
304 stainless steel	SR	5JB-08GSR
316L stainless steel	SV	5JB-08GSV
316Ti stainless steel	SY	5JB-08GSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	5JB-08GZ	96	360
Durakote plating	ZD	5JB-08GZD	360	720
Zinc-nickel plating	ZN	5JB-08GZN	1000	-