


1JT-SP

JIC MALE 74° CONE / BSPT MALE

PART NO.	THREAD		DIMENSIONS						
	E	F			A	B	L	S1	
1JT-04SP	7/16"X20	R1/4"X19			14	14.5	34.5	14	
1JT-04-02SP	7/16"X20	R1/8"X28			14	10	30	12	
1JT-04-06SP	7/16"X20	R3/8"X19			14	15	35	17	
1JT-04-08SP	7/16"X20	R1/2"X14			14	20	41	24	
1JT-05-02SP	1/2"X20	R1/8"X28			14	10.5	30.5	14	
1JT-05-04SP	1/2"X20	R1/4"X19			14	14.5	34	14	
1JT-05-06SP	1/2"X20	R3/8"X19			14	15	35	17	
1JT-06SP	9/16"X18	R3/8"X19			14.1	15	34	17	
1JT-06-02SP	9/16"X18	R1/8"X28			14.1	10.5	30.5	17	
1JT-06-04SP	9/16"X18	R1/4"X19			14.1	14.5	34	17	
1JT-06-08SP	9/16"X18	R1/2"X14			14.1	20	41	22	
1JT-06-12SP	9/16"X18	R3/4"X14			14.1	20	43.5	30	
1JT-08SP	3/4"X16	R1/2"X14			16.7	20	44.5	22	
1JT-08-04SP	3/4"X16	R1/4"X19			16.7	14.5	39	22	
1JT-08-06SP	3/4"X16	R3/8"X19			16.7	15	39	22	
1JT-08-10SP	3/4"X16	R5/8"X14			16.7	19	43.5	24	
1JT-08-12SP	3/4"X16	R3/4"X14			16.7	20	46	30	
1JT-08-16SP	3/4"X16	R1"X11			16.7	25.5	52	36	
1JT-10-06SP	7/8"X14	R3/8"X19			19.3	15	42.5	24	
1JT-10-08SP	7/8"X14	R1/2"X14			19.3	20	46.5	24	
1JT-10SP	7/8"X14	R5/8"X14			19.3	19	46.5	24	
1JT-10-12SP	7/8"X14	R3/4"X14			19.3	20	48.5	30	
1JT-10-16SP	7/8"X14	R1"X11			19.3	25.5	54.5	36	
1JT-12SP	1.1/16"X12	R3/4"X14			21.9	20	51	30	
1JT-12-06SP	1.1/16"X12	R3/8"X19			21.9	15.5	47.5	30	
1JT-12-08SP	1.1/16"X12	R1/2"X14			21.9	20	51	30	
1JT-12-16SP	1.1/16"X12	R1"X11			21.9	25.5	57.5	36	
1JT-12-20SP	1.1/16"X12	R1.1/4"X11			21.9	26.5	61.5	46	
1JT-14-12SP	1.3/16"X12	R3/4"X14			22.6	20	52.5	32	
1JT-14-16SP	1.3/16"X12	R1"X11			22.6	25.5	58.5	36	
1JT-16SP	1.5/16"X12	R1"X11			23.1	25.5	59	36	
1JT-16-08SP	1.5/16"X12	R1/2"X14			23.1	20	53	36	
1JT-16-12SP	1.5/16"X12	R3/4"X14			23.1	20	53	36	
1JT-16-20SP	1.5/16"X12	R1.1/4"X11			23.1	26.5	61.5	46	
1JT-16-24SP	1.5/16"X12	R1.1/2"X11			23.1	26.5	64.5	50	
1JT-20SP	1.5/8"X12	R1.1/4"X11			24.3	26.5	63	46	
1JT-20-12SP	1.5/8"X12	R3/4"X14			24.3	20	59	46	
1JT-20-16SP	1.5/8"X12	R1"X11			24.3	25.5	62.5	46	
1JT-20-24SP	1.5/8"X12	R1.1/2"X11			24.3	26.5	66.5	50	
1JT-24SP	1.7/8"X12	R1.1/2"X11			27.5	26.5	69	50	
1JT-24-16SP	1.7/8"X12	R1"X11			27.5	25.5	67.5	50	



**1JT-SP**

JIC MALE 74° CONE / BSPT MALE

PART NO.	THREAD		DIMENSIONS					
	E	F	A	B	L	S1		
1JT-24-20SP	1.7/8"X12	R1.1/4"X11	27.5	26.5	67.5	50		
1JT-24-32SP	1.7/8"X12	R2"X11	27.5	30	74.5	65		
1JT-32SP	2.1/2"X12	R2"X11	33.9	30	80	65		
1JT-32-24SP	2.1/2"X12	R1.1/2"X11	33.9	26.5	77.5	65		
1JT-40SP	3"X12	R2.1/2"X11	35.5	34	87.5	80		

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	CJ-08Z
304 stainless steel	SR	CJ-08SR
316L stainless steel	SV	CJ-08SV
316Ti stainless steel	SY	CJ-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	CJ-08Z	96	360
Durakote plating	ZD	CJ-08ZD	360	720
Zinc-nickel plating	ZN	CJ-08ZN	1000	-