



AFFO-OG

ORFS MALE O-RING / ADJUSTABLE SAE O-RING SEAL S-SERIES ISO 11926-2 RUN TEE

PART NO.	THREAD			O-RING			DIMENSIONS				
	E	F	G	E	F	G	A	B	C	S1	S2
AFFO-04OGZ	9/16"X18	9/16"X18	7/16"X20	O011	O011	O904	23	23	30	14	17
AFFO-04-04-06OGZ	9/16"X18	9/16"X18	9/16"X18	O011	O011	O906	23	23	32	14	22
AFFO-06OGZ	11/16"X16	11/16"X16	9/16"X18	O012	O012	O906	27.5	27.5	35.5	19	22
AFFO-06-06-08OGZ	11/16"X16	11/16"X16	3/4"X16	O012	O012	O908	27.5	27.5	38	19	24
AFFO-08-08-06OGZ	13/16"X16	13/16"X16	9/16"X18	O014	O014	O906	31	31	37.5	22	22
AFFO-08OGZ	13/16"X16	13/16"X16	3/4"X16	O014	O014	O908	31	31	40.5	22	24
AFFO-08-08-10OGZ	13/16"X16	13/16"X16	7/8"X14	O014	O014	O910	31	31	45.3	22	30
AFFO-08-08-12OGZ	13/16"X16	13/16"X16	1.1/16"X12	O014	O014	O912	34.5	34.5	52	27	36
AFFO-10OGZ	1"X14	1"X14	7/8"X14	O016	O016	O910	36.5	36.5	50.8	27	30
AFFO-10-10-12OGZ	1"X14	1"X14	1.1/16"X12	O016	O016	O912	36.5	36.5	52	27	36
AFFO-12OGZ	1.3/16"X12	1.3/16"X12	1.1/16"X12	O018	O018	O912	40.3	40.3	55.3	30	36
AFFO-16-16-12OGZ	1.7/16"X12	1.7/16"X12	1.1/16"X12	O021	O021	O912	44.5	44.5	59.5	36	36
AFFO-16OGZ	1.7/16"X12	1.7/16"X12	1.5/16"X12	O021	O021	O916	44.5	44.5	59.3	36	41
AFFO-20OGZ	1.11/16"X12	1.11/16"X12	1.5/8"X12	O025	O025	O920	47.5	47.5	60.5	41	50
AFFO-24OGZ	2"X12	2"X12	1.7/8"X12	O029	O029	O924	53.5	53.5	68.5	50	55

1. Material options for connector and the O-ring.

Connector material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	AFFO-08OGZ
304 stainless steel	Viton	SR	AFFO-08OGSR
316L stainless steel	Viton	SV	AFFO-08OGSV
316Ti stainless steel	Viton	SY	AFFO-08OGSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	AFFO-08OGZ	96	360
Durakote plating	ZD	AFFO-08OGZD	360	720
Zinc-nickel plating	ZN	AFFO-08OGZD	1000	-