


**2NU9-L**

LONG NPT MALE/NPSM FEMALE 60° CONE 90° ELBOW

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	S1	S2	
2NU9-04LZ	Z1/4"X18	1/4"X18			40.1	4.6	14	19	
2NU9-06LZ	Z3/8"X18	3/8"X18			46.2	6	19	22	
2NU9-08LZ	Z1/2"X14	1/2"X14			55.1	7.5	22	27	
2NU9-12LZ	Z3/4"X14	3/4"X14			62	8.9	27	32	
2NU9-16LZ	Z1"X11.5	1"X11.5			76.5	10.5	33	41	
2NU9-20LZ	Z1.1/4"X11.5	1.1/4"X11.5			93.7	11.2	41	50	
2NU9-24LZ	Z1.1/2"X11.5	1.1/2"X11.5			104.1	11.2	48	55	
2NU9-32LZ	Z2"X11.5	2"X11.5			122.2	11.2	63	70	

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2NU9-08LZ
304 stainless steel	SR	2NU9-08LSR
316L stainless steel	SV	2NU9-08LSV
316Ti stainless steel	SY	2NU9-08LSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2NU9-08LZ	96	360
Durakote plating	ZD	2NU9-08LZD	360	720
Zinc-nickel plating	ZN	2NU9-08LZN	1000	-