

**4B-WD**

BSP MALE CAPTIVE SEAL PLUG

PART NO.	THREAD		CAPTIVE SEAL	DIMENSIONS					
	E			A	L	S1			
4B-02WDZ	G1/8"X28		WD-B02	8	15.5	14			
4B-04WDZ	G1/4"X19		WD-B04	12	19.6	19			
4B-06WDZ	G3/8"X19		WD-B06	12	22.5	22			
4B-08WDZ	G1/2"X14		WD-B08	14	25	27			
4B-12WDZ	G3/4"X14		WD-B12	16	29	32			
4B-16WDZ	G1"X11		WD-B16	18	35	41			
4B-20WDZ	G1.1/4"X11		WD-B20	20	37	50			
4B-24WDZ	G1.1/2"X11		WD-B24	22	40	55			

1. Material options for connector body and the Captive seal.

Connector body material	Captive seal material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	4B-08WDZ
304 stainless steel	Viton	SR	4B-08WDSR
316L stainless steel	Viton	SV	4B-08WDSV
316Ti stainless steel	Viton	SY	4B-08WDSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4B-08WDZ	96	360
Durakote plating	ZD	4B-08WDZD	360	720
Zinc-nickel plating	ZN	4B-08WDZN	1000	-