



4HN-N

METRIC MALE L-SERIES HOLLOW HEX PLUG ISO 6149-3

PART NO.	THREAD		O-RING		DIMENSIONS						
	E		E		A	L	S1				
4HN-10NZ	M10X1		O08.1X1.6		9.5	13.5	5				
4HN-12NZ	M12X1.5		O09.3X2.4		11	15.5	6				
4HN-14NZ	M14X1.5		O11.3X2.4		11	16	6				
4HN-16NZ	M16X1.5		O13.3X2.4		12.5	17.5	8				
4HN-18NZ	M18X1.5		O15.3X2.4		14	19	8				
4HN-22NZ	M22X1.5		O19.3X2.4		15	20	10				
4HN-27NZ	M27X2		O23.5X3.0		18.5	23.5	12				
4HN-33NZ	M33X2		O29.5X3.0		18.5	24.5	14				
4HN-42NZ	M42X2		O38.5X3.0		19	25	17				
4HN-48NZ	M48X2		O44.5X3.0		17.5	20.5	24				

1. Material options for connector body and the O-ring.

Connector body material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	4HN-22NZ
304 stainless steel	Viton	SR	4HN-22NSR
316L stainless steel	Viton	SV	4HN-22NSV
316Ti stainless steel	Viton	SY	4HN-22NSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4HN-22NZ	96	360
Durakote plating	ZD	4HN-22NZD	360	720
Zinc-nickel plating	ZN	4HN-22NZN	1000	-